

MJ Lighting Source Co.,Ltd


Alice:wangzuxia2010@hotmail.com Mobile :0086-13534016771

website:<http://www.mjlightingled.com/>

Specification for DMX512

Pictures:

Pictures of DMX512 Controller



Features:


1. One port controls maximum 2048 pixels
2. There are 102 kinds of patterns internal, SD also supported
3. Under SD state, it is available to choose the pattern and speed internal.
4. Multiple controllers can be cascade, and synchronization signal can't be over 50 meters.
5. Distance between control and light no longer than 15meters.
6. Voltage: 5V/DC5-24V
7. Once turned on, it will check whether there is SD card automatically, If there is, it will use the pattern in SD, Otherwise, will use the patterns internal the controllers

IC Supported

TM1803, TM1804, TM1913, TM1809, TM1812, TM1914, TM1829, UCS2903, UCS2909, UCS2912, UCS1903, UCS1909, UCS1912, **WS2801, WS2812, WS2811**
LDP6803, LDP8806, LDP1109, D705, SM16716, SM16726, 16703, DMX512, APA102



Multiple controllers cascade

Multiple controllers cascade, connect picture.





How to use

1. Choose the right IC.



Press ON/OFF, When it display OFF, Then press MODE/Speed to choose the IC mode. After doing it, Press ON/OFF to quit out.

2. Setting Pixel quantity



Press ON/OFF, When it display OFF, Then press UP/DOWN to setting the quantity. After doing it, Press ON/OFF to quit out.

Package

